



## TABLA DE DIMENSIONAMIENTO

| Tanque  | E/S   | D     | Zeosorb®<br>Pie³ | Flujo GPM            |                       |                     | Retrolavado |        |
|---------|-------|-------|------------------|----------------------|-----------------------|---------------------|-------------|--------|
|         |       |       |                  | Lento <sup>(1)</sup> | Normal <sup>(2)</sup> | Pico <sup>(3)</sup> | Mínima      | Máxima |
| 9"x48"  | 1"    | 0.75" | 1                | 3.5                  | 5.3                   | 7.1                 | 4.4         | 8.8    |
| 10"x54" | 1"    | 0.75" | 1.5              | 4.4                  | 6.5                   | 8.7                 | 5.5         | 11     |
| 12"x52" | 1"    | 0.75" | 2                | 6.3                  | 9.4                   | 12.6                | 7.9         | 16     |
| 13"x54" | 1"    | 1"    | 2.5              | 7.4                  | 11                    | 15                  | 9.2         | 18     |
| 14"x65" | 1.25" | 1"    | 3                | 9                    | 13                    | 17                  | 11          | 21     |
| 16"x65" | 1.25" | 1"    | 4                | 11                   | 17                    | 22                  | 14          | 28     |
| 18"x65" | 1.25" | 1"    | 5                | 14                   | 21                    | 28                  | 18          | 35     |
| 21"x62" | 1.25" | 1.5"  | 7                | 19                   | 29                    | 38                  | 24          | 48     |
| 24"x72" | 1.5"  | 1.5"  | 10               | 25                   | 38                    | 50                  | 31          | 63     |
| 30"x72" | 2"    | 2"    | 15               | 39                   | 59                    | 79                  | 49          | 98     |
| 36"x72" | 2"    | 2.5"  | 20               | 57                   | 85                    | 113                 | 71          | 141    |
| 42"x72" | 2"    | 3"    | 30               | 77                   | 115                   | 154                 | 96          | 192    |
| 48"x72" | 3"    | 4"    | 40               | 101                  | 151                   | 201                 | 126         | 251    |

**1** Calculado en base de 8 gpm/pie², para aguas residuales tratadas, agua con gran cantidad de sólidos suspendidos, etc.

**2** Calculado en base de 12 gpm/pie², para agua de buena calidad, pre-tratamiento de ósmosis inversa, potabilización de aguas.

**3** Calculado en base de 16 gpm/pie², para aguas de excelente calidad, picos intermitentes de flujo durante el día.